

BOART LONGYEAR DIAMOND CORING BITS

Q= System used T=Thin K=Kerf

3= Triple Tube U=Underground

SIZE	CORE SIZE	HOLE SIZE	SIZE	CORE SIZE	HOLE SIZE
AQ, AQ-U	27.0	48.0	LTK46	35.6	46.0
AQ, AQTK-U	30.5	48.0	LTK48	35.6	48.0
BQ, BQ-U	36.4	60.0	LTK56	45.2	56.0
BQTK, BQTK-U	40.7	60.0	LTK60	45.2	60.0
NQ, NQ-U	47.6	75.7			
NQ2", NQ2"-U	50.6	75.7	HD/CHD76	43.5	75.7
HQ, HQ-U	63.5	96.0	HD/CHD101	63.5	101.3
PQ	85.0	122.6	CHD134	85.0	134.0
BQ-3	33.5	60.0	RWG	18.7	29.8
NQ-3	45.0	75.7	EWG, EWM, EWL	21.5	37.7
HQ-3	61.1	96.0	AWG, AWM, AWL	30.1	48.0
PQ-3	83.0	122.6	BWG, BWM, BWL	42.0	60.0
			NWG, NWM, NWL	54.7	75.7
			HWG	76.2	99.2

HAGBY METRIC THIN WALL WIRELINE SYSTEM

wl = wire line

* = Available with extra inner tubes

SIZE	ROD OD (MM)	ROD ID (MM)	HOLE SIZE (MM)	CORE SIZE (MM)
WL46	43.2	35.2	46.8	28.8
WL56	53.2	45.2	56.8	39.0
WL66	63.9	57.0	66.3	50.5
WL66-3*	63.9	57.0	66.3	45.0
WL76	73.2	64.4	76.3	57.5
WL76-3*	73.2	64.4	76.3	52.0

W SERIES FLUSH JOINT CASING

SIZE	ROD ID (INCH)	ROD ID (MM)	ROD OD (INCH)	ROD OD (MM)
RW	1 3/16	30.2	1 7/16	36.5
EW	1 1/2	38.1	1 13/16	46.0
AW	1 29/32	48.4	2 1/4	57.1
BW	2 3/8	60.3	2 7/8	73.0
NW	3	76.2	3 1/2	88.9

HW	4	101.6	4 1/2	114.3
PW	5	127.0	5 1/2	139.7
SW	6	152.4	6 5/8	168.3
VW	7	177.8	7 5/8	193.7
ZW	8	203.2	8 5/8	219.1

BRADLEY MANUFACTURING

W/L = WIRE LINE

SIZE	ID (INCH)	ID (MM)	OD (INCH)	OD (MM)	HOLE SIZE (MM)	CORE SIZE (MM)
A W/L	1 3/8	34.9	1 3/4	44.5	48.0	27
B W/L	1 13/16	46	2 1/5	55.6	59.9	36.4
N W/L	2 3/8	60.3	2 3/4	69.9	75.7	47.6
H W/L	3 1/16	77.8	3 1/2	88.9	96.1	63.5
P W/L	4.062	103.2	4.625	117.5	122.6	85

BRADLEY MANUFACTURING

TW = THIN WALL

SIZE	ID (INCH)	ID (MM)	OD (INCH)	OD (MM)	HOLE SIZE (MM)	CORE SIZE (MM)
ATW	1.44	36.5	1.75	44.5	48.0	30.3
BTW	1.91	48.5	2.23	55.6	60.0	42.0
NTW	2.53	64.1	2.88	69.9	75.7	56.0